

4000 Series Tamperproof Outlet



Features & Benefits

- ✕ High Density, Single Gang 4 Port
- ✕ Tamperproof design
- ✕ Enhanced Category 5 Performance
- ✕ Patent Pending
- ✕ Designed for direct wall mounting
- ✕ Custom logo service available

Originally designed for the education sector, these high-density Enhanced Category 5 Outlets restrict the user's access to the patch lead. This eliminates one of the most common causes of network problems and will give the Network Administrator one thing less to worry about.

Offering the same performance as the 4020, the 4030 outlet has the added benefit that leads cannot be unplugged without removing the cover, thus increasing system integrity.

Like the other Wall Outlets in the Connectix 4000 Series, they are extremely quick and easy to install. Just attach the base plate to the wall, snap in the PCB, punch down the cables and install the cover. Gone are the problems of installing modules into a faceplate and pushing excess wires in a back box.

Designed for direct wall mounting with top entry Mini Trunking, an optional spacer plate allows for side cable entry. In addition, they fit over standard back boxes to provide maximum mounting flexibility.

With 4 ports in a single gang box there is no other product offering the same combination of density and security.

Ordering Information

Product Description	Part Number
4030, 4 Way Tamperproof Wall Outlet	008-001-012-01
4100 Entry Spacer plate	008-001-013-01

Specification

Width	87mm
Depth	27mm
Height	105mm
Spacer Plate Depth	8mm
Material	ABS thermoplastic resin, with grade UL94 VO at 1.5mm flame retardancy
Finish	High Gloss
IDC Blocks	4 Way Industry Standard IDC blocks
PCB	1.6mm double sided PTH Boards
Conforms to	TIA/EIA-568-B Enhanced Category 5 Specification

Simple Assembly Sequence

