

4000 Series Shuttered Outlet



Features & Benefits

- ✕ High Density, Single Gang 4 Port
- ✕ Category 6 and Enhanced Category 5 versions
- ✕ Unused jacks protected by shutters
- ✕ Designed for direct wall mounting
- ✕ Custom logo service available

Performance does not have to be bulky, and the Connectix 4 Way Shuttered Wall outlet proves it. Available for Category 6 and Enhanced Category 5 Systems, these 4 Way Shuttered Outlets combine high performance, high density and shutter protected sockets in a single gang package.

Like the other Wall Outlets in the Connectix 4000 Series, they are extremely quick and easy to install. Just attach the base plate, snap in the PCB, punch down the cables and install the cover. Gone are the problems of installing modules into a faceplate and pushing excess wires in a back box.

Designed for direct wall mounting with top entry Mini Trunking, an optional spacer plate allows for side and bottom cable entry. In addition, they fit over standard back boxes to provide maximum mounting flexibility.

With 4 ports in a single gang box there is no other product offering the same combination of performance and packaging density.

Ordering Information

Product Description	Part Number
4015 Cat 6, 4 Way Shuttered Outlet	008-001-010-01
4010 Enhanced Cat 5, 4 Way Shuttered Outlet	008-001-010-05
4100 Entry Spacer plate	008-001-013-01

Specification

Width	87mm
Depth	27mm
Height	87mm
Spacer Plate Depth	8mm
Material	ABS thermoplastic resin, with grade UL94 VO at 1.5mm flame retardancy
Finish	High Gloss
IDC Blocks	4 Way Industry Standard IDC blocks
PCB	1.6mm double sided PTH Boards
Conforms to	4015: TIA/EIA-568-B.2-1 Category 6 Specification 4010: TIA/EIA-568-B Enhanced Category 5 Specification

Simple Assembly Sequence

