



## Features & Benefits

- ✕ Light Gauge 25mm Overall Diameter
- ✕ Extra Super High Impact material
- ✕ Meets all the relevant standards
- ✕ Quick and easy to install
- ✕ Large range of fittings available

The Connectix Conduit range is manufactured by Marshall Tufflex. It is manufactured from PVC-U, which has been specially formulated to meet the requirements of BS EN 50086, BS4607, BS6099 and BS7671 (Wiring Regulations).

The conduit is produced in Extra Super High Impact material which is capable of withstanding the most hazardous conditions on site and which exceeds the most stringent requirements of the British standards.

The range includes a wide variety of plain bored circular boxes in various through, angle and tee configurations. The boxes are suitable for suspending a load of up to 3kg centrally at 60°C maximum.

## Ordering Information

Product Description	Part Number
25mm Conduit 3 Metre (CR3)	012-002-010-25I
Circular Lid 50mm Flush (MCL1)	012-002-017-00I
25mm Coupler (MC3)	011-004-025-04
25mm Inspection Bend (MIB3)	012-002-012-25I
25mm Plain Bend (MNB3)	012-002-011-25I
25mm Female Adapter (MAB3)	012-002-015-25I
25mm Male Adapter (MA3)	012-002-014-25I
25mm Spacebar Saddle (MSB3)	012-002-009-00I
25mm Through Box (3MRB3)	012-002-016-25I