

## Features & Benefits

- ✕ High Density, Single Gang 4 Port
- ✕ Enhanced Category 5 Performance
- ✕ No protruding leads
- ✕ Designed for direct wall mounting
- ✕ Custom logo service available
- ✕ Also available in a 2 Port version



## Ordering Information

Product Description	Part Number
4020, 4 Way Vertical Wall Outlet	008-001-011-01
4022, 2 Way Vertical Wall Outlet	008-001-011-03
4100 Entry Spacer plate	008-001-013-01

## Specification

Width	87mm
Depth	27mm
Height	87mm
Spacer Plate Depth	8mm
Material	ABS thermoplastic resin, with grade UL94 VO at 1.5mm flame retardancy
Finish	High Gloss
IDC Blocks	4 Way Industry Standard IDC blocks
PCB	1.6mm double sided PTH Boards
Conforms to	TIA/EIA-568-B Enhanced Category 5 Specification

The 4020 Vertical Wall Outlet offers Enhanced Category 5 performance in a high-density package. The position of the sockets allows for a compact installation without protruding leads.

Like the other Wall Outlets in the Connectix 4000 Series, they are extremely quick and easy to install. Just attach the base plate, snap in the PCB, punch down the cables and install the cover. Gone are the problems of installing modules into a faceplate and pushing excess wires in a back box.

Designed for direct wall mounting with top entry Mini Trunking, an optional spacer plate allows for side cable entry. In addition, they fit on standard back boxes to provide maximum mounting flexibility.

## Simple Assembly Sequence

